

## **SOLUTION 5 WIDESCREEN BIOETHANOL**

| Supplier name              | Arada      |  |
|----------------------------|------------|--|
| Product Code               | SOL5WS-BIO |  |
| Dimensions                 |            |  |
| Width (inc. Floor Fixings) | 525 mm     |  |
| Height (inc. Hot Plate)    | 558 mm     |  |
| Depth (inc. Door Handle)   | 382 mm     |  |





## Performance


| Fuel Type                                   | Bioethanol     |
|---|----------------|
| Burner capacity (Max inc. Overfill 1 Litre) | 0.8 Litre      |
| Nominal Heat Output<br>To Room              | 2.46 kW        |
| Max Burn Rate                               | 0.31 L / Hr    |
| Typical Run Time (approximate)              | 2.5 to 4.5 Hrs |


## **Features**

| Stove body type                              | Freestanding                                  |
|--|---|
| Body thickness                               | 3mm Steel                                     |
| Cast Iron door                               | Yes   |
| Optional decorative flue compatibility       | Fits standard 5inch flue collar and flue pipe |
| Suitable for non-<br>combustible 12mm hearth | Yes   |
| Nett Weight                                  | 46 Kg   |
| Gross Weight                                 | 52.6 Kg                                       |









## Minimum Distance to Surrounding Materials

| Install location | Rear   | Per Side | Тор    | Notes                                  |
|------------------|--------|----------|--------|--|
| Alcove or recess | 50 mm  | 75 mm    | 200 mm | Included limit screws must be fitted * |
| Freestanding     | 100 mm | 200 mm   | 300 mm | Included limit screws not required *   |

Specific precautions to be taken when the local space heater is assembled, installed or maintained:

 $Product \ should \ be \ installed \ in \ accordance \ with \ local \ building \ regulations. \ Appliance \ will \ become \ very \ hot \ during \ use.$ 

An approved (BS-EN 50291) and working Carbon Monoxide (CO) alarm should be installed in the same room where the appliance is being fired.

\* For more information please refer to document (BK778) Bioethanol Stove User Guide section 3.4

Installation and operating instructions for this stove are available online at  $\underline{www.aradastoves.com/support}$ 

BK999 / SOL5WS-BIO 25/11/2024